



Patent
Attorney's Docket No. 033275-316

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Patent Application of)
)
Alexander BEECK, et al.) Group Art Unit: Unassigned
)
Application No.: 10/002,141) Examiner: Unassigned
)
Filed: December 5, 2001)
)
For: COMPONENT OF A FLOW MACHINE,)
WITH INSPECTION APERTURE)

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Prior to examination of the above-captioned patent application, it is requested that the following amendments be entered.

IN THE SPECIFICATION:

Please replace the verified English translated specification (being filed on even date herewith) with the attached substitute specification. A marked-up copy of the specification is provided to show the changes made from the verified English translated specification, and no new matter has been added.

IN THE CLAIMS:

Please amend Claims 1-7 as follows:

1. (Amended) A component of a flow machine, comprising:
a plurality of cooling channels for passage of a cooling medium;
at least one inspection aperture through which an inspection of the interior of the component is made possible;

the inspection aperture being arranged and dimensioned such that it forms a dust discharge aperture for dust or dirt particles contained in the cooling medium.

2. (Amended) The component according to claim 1, wherein the inspection aperture is dimensioned such that it makes possible the introduction of a borescope.

3. (Amended) The component according to claim 1 or 2, wherein the component is a rotating blade for a turbine, and the inspection aperture is arranged in the neighborhood of a tip of the blade.

4. (Amended) The component according to claim 3, wherein the inspection aperture runs approximately parallel to the machine axis.

5. (Amended) The component according to claim 3, wherein the inspection aperture is arranged at the blade tip and runs in a radial direction.

6. (Amended) A process for at least one of the inspection and the cleaning of the interior of a component of a flow machine, said component constructed according to claim 1, wherein the process comprises:

introducing at least one of an inspection tool and a cleaning tool through the inspection or dust discharge aperture, and performing at least one of an inspection of and a cleaning of the interior of the component with the at least one of an inspection tool and a cleaning tool.

7. (Amended) The process according to claim 6, wherein a borescope is used as the inspection tool.

REMARKS

By way of the foregoing amendments to the claims, Claims 1-7 have been amended for clarification without in any way narrowing the scope of the claims, and a substitute specification has been provided to clarify and place the specification into proper idiomatic English. These changes have been made in accordance with 37 C.F.R. § 1.121 as amended on November 7, 2000. Marked-up versions of Claims 1-7 indicating the changes accompany this Preliminary Amendment, along with a marked-up copy of the specification showing the changes made by the substitute specification. No new matter has been added.

Early and favorable consideration with respect to this application is respectfully requested.

Should any questions arise in connection with this application, the undersigned respectfully requests that he be contacted at the number indicated below.

Respectfully submitted,
BURNS, DOANE, SWECKER & MATHIS, L.L.P.

By: William O. Trousdel
William O. Trousdel
Registration No. 38,637

P. O. Box 1404
Alexandria, Virginia 22313-1404
(703) 836-6620

Date: March 12, 2002



VERSION OF CLAIMS WITH MARKINGS TO SHOW CHANGES MADE

Patent Claims

1. ~~[Component]~~ **(Amended) A component** of a flow machine, ~~in particular a~~
gas turbine, which has] **comprising:**
a plurality of cooling channels ~~[(4)]~~ for **passage of** a cooling medium ~~[and also]~~;
at least one inspection aperture ~~[(5)]~~ through which an inspection of the interior of the
component is made possible;
wherein]
the inspection aperture ~~[(5)] is~~ **being** arranged and dimensioned such that it forms a
dust discharge aperture for dust or dirt particles contained in the cooling medium.
2. ~~[Component]~~ **(Amended) The component** according to claim 1, wherein the
inspection aperture ~~[(5)]~~ is dimensioned such that it makes possible the introduction of a
borescope.
3. ~~[Component]~~ **(Amended) The component** according to claim 1 or 2, wherein
~~[it]~~ **the component** is ~~[constituted as]~~ a rotating blade for a turbine, **and** the inspection
aperture ~~[(5)] being~~ **is** arranged in the neighborhood of **a tip of** the blade ~~[tip]~~.
4. ~~[Component]~~ **(Amended) The component** according to claim 3, wherein the
inspection aperture ~~[(5)]~~ runs approximately parallel to the machine axis.
5. ~~[Component]~~ **(Amended) The component** according to claim 3, wherein the
inspection aperture ~~[(5)]~~ is arranged at the blade tip and runs in a radial direction.
6. ~~[Process for]~~ **(Amended) A process for at least one of** the inspection
~~[and/or]~~ **and the** cleaning of the interior of a component ~~[, embodied according to patent~~
claim 1, of a flow machine, in particular a gas turbine, wherein an inspection and/or] **of a**

flow machine, said component constructed according to claim 1, wherein the process comprises:

introducing at least one of an inspection tool and a cleaning tool ~~[is introduced]~~ through the inspection or dust discharge aperture, and **performing at least one of** an inspection ~~[and/or]~~ **of and a** cleaning of the interior of the component ~~[is carried out]~~ with the **at least one of an** inspection ~~[and/or]~~ **tool and a** cleaning tool.

7. ~~[Process]~~**(Amended) The process** according to claim 6, wherein a borescope is used as the inspection tool.

U.S. PATENT & TRADEMARK OFFICE

SUBSTITUTE SPECIFICATION

033275-316

COMPONENT OF A FLOW MACHINE, WITH INSPECTION APERTURE

Field of the Invention

[0001] The present invention relates to a component of a flow machine, particularly of a gas turbine, which has cooling channels for a cooling medium and also at least one inspection aperture through which an inspection of the interior of the component is made possible, and also a process for the inspection and/or cleaning of the interior of such a component.

Background of the Invention

[0002] For the attainment of a high efficiency factor, modern high temperature gas turbines require a carefully devised cooling system, particularly for the cooling of the highly loaded turbine blades. The turbine blades have for this purpose one or more chambers and/or channels constructed as cavities, via which a cooling medium can be supplied to the blades from the rotor side. As a rule, numerous cooling air bores are provided at the leading region of the turbine blades at their forward edge, and the cooling medium can emerge through them from the interior of the blade. A cooling air film forms on the surface in this region and protects the turbine blade from excessive heating. In the same way, corresponding cooling air bores are also present at the rear edge of the turbine blade.

[0003] A problem with such hollow components, such as turbine blades or combustion chamber elements, which are frequently cast in one piece, is represented by the poor accessibility of the interior of these components. Their inspection, for example for internal damage such as cracks, or for dirt deposits, is therefore as a rule difficult.

[0004] To avoid this problem, it is known, for example from DE 198 01 804 A1, to install, in addition to the cooling air bores which are necessary in each case, one or more inspection access apertures in the outer wall of the turbine blade, through which bores the blade interior can be investigated with a corresponding inspection tool. Such an inspection aperture or inspection access aperture also makes possible the inspection of an already

built-in turbine blade, and also the cleaning from the interior of the turbine blade of dirt deposits which could lead to blockage of the very narrow cooling air bores. The document provides for the introduction of a special cleaning tool through the inspection access aperture for this purpose.

Summary of the Invention

[0005] The present invention provides a hollow component of a flow machine, such as a turbine engine, in such a manner that both the inspection and also a reduction of the danger of a blockage of the cooling air bores can be implemented in a simple manner.

[0006] The component with cooling channels for a cooling medium and also at least one inspection aperture through which inspection of the interior of the component is made possible is characterized in that the inspection aperture is arranged on the component, and is dimensioned, in such a manner that it simultaneously forms a dust discharge aperture for dust or dirt particles contained in the cooling medium.

[0007] A "dust discharge aperture" refers to an aperture in the wall of the component by means of which particles entrained in the cooling medium emerge from the interior of the component due to their inertia. A dust discharge aperture should therefore be arranged at a deflection of the channel conducting the cooling medium or at the end of a dust channel branching from this channel at a corresponding deflection. Such dust discharge apertures are already used in components of flow machines in order to prevent a blockage of the cooling channel bores. An example of an embodiment of a turbine blade with such a dust discharge aperture can be gathered from U.S. Patent 4,820,122, for example. The interior of the turbine blade here has cooling air channels which run in a serpentine manner. The branching into the individual serpentine channels takes place in the region of the entry of the cooling air into the turbine blade at the rotor. A straight channel extends radially as a direct extension of the inlet channel and leads directly to a dust discharge aperture at the blade tip. Particles entering with the cooling air are conveyed, due to the force of the cooling air, directly in a straight line radially to this dust discharge aperture, while nearly dirt-free air can enter the other serpentine channels without problems. The dust particles are thus conducted out of the cooling channels

into the open air through this dust discharge aperture or this dust hole, so that the cooling air bores are not blocked by the dust particles.

[0008] The inventor of the present invention has now discovered that inspection access apertures, by skillful arrangement, can fulfill the function of dust discharge apertures, or that dust discharge apertures, by suitable dimensioning, particularly enlargement, can serve as inspection access apertures. The dust discharge apertures according to the invention are designed in size and position both so that dust is favorably discharged and also an aperture with sufficient diameter is formed in order to be able to introduce a borescope through this aperture.

[0009] The inspection aperture or inspection bore, which at the same time represents a dust discharge aperture, is preferably already considered when the component is cast and not, as is the case with the cooling air apertures, introduced by subsequent drilling. In rotating blades, this inspection and dust discharge aperture is preferably located in the neighborhood of the blade tip. In order to be able to inspect these blades even in the built-in state of the machine, these inspection and dust discharge apertures are to be arranged approximately parallel to the machine axis, if the inspection tool is to be introduced in the hot gas path of the gas turbine. If the inspection tool is to be introduced radially into the machine, a position at the blade tip is more favorable in which the inspection and dust discharge aperture runs radially of the machine axis. By the combination according to the invention of the dust discharge and the inspection function in one and the same aperture, unnecessary apertures are avoided which can lead to an undesired loss of cooling medium and thus bring about a loss of efficiency.

Brief Description of the Drawings

[0010] The invention is described below with reference to the embodiments shown in the accompanying drawing, without limitation of the general concept of the invention in any way.

[0011] Fig.1 is a diagram schematically showing a section through a turbine blade in accordance with an embodiment of the invention.

[0012] Fig. 2 is a further example, in cross section, of a turbine blade according to another embodiment of the present invention.

Detailed Description of the Preferred Embodiments

[0013] Fig. 1 schematically shows in cross section a turbine blade with a blade foot 1, platform 2, and blade 3. Cooling air is supplied to the turbine blade from the blade foot 1 by means of the cavity 4 visible in the cross section. A dust discharge aperture 5 is shown at the blade tip in the forward region, i.e., in the leading region of the turbine blade, and dirt particles entrained with the cooling medium are discharged, due to their inertia, from the hollow channel 4 through the said dust discharge aperture 5. Due to the high flow speed of the cooling medium at the deflection of the cooling channel 4 present at the dust discharge aperture 5, the particles, due to their large mass, take the path through the dust discharge aperture 5 and do not pass via the deflection into the further course of the cooling channel, in which relatively dust-free air thus flows. The cooling air flows past the pins 6 and leaves the blade by means of apertures at the rear edge, for example, by means of a slit.

[0014] The dust discharge aperture 5 is, according to the invention, constituted with a large enough diameter for the introduction of a borescope to be possible through this aperture 5 into the interior of the turbine blade. In this manner, the interior of this component can be inspected at any time, even in the built-in state.

[0015] Finally, Fig. 2 shows a further example, in which the dust discharge aperture 5 however runs, not radially, but in the axial direction. In this example also, the blade foot 1, platform 2, and turbine blade 3 can again be seen in cross section. The cooling channel 4 runs in the same way as in Fig. 1. The dust hole 5, which in this example runs parallel to the machine axis, makes inspection possible with an inspection tool introduced in the hot gas path. The mechanism of dust extraction is the same as that in Fig. 1. In this example, the dirt particles, due to their inertia and the high flow speed of the deflected cooling medium, take the path via the channel 7 leading to the dust hole 5, while the cooling medium is deflected at the branch without problems in the direction toward the machine axis and is therefore conducted, relatively dust-free, past the pins 6 to the cooling air apertures at the rear edge of

the blade. The dust hole 5 or the channel 7 leading to this are hence again constituted with a large enough diameter for the introduction of an inspection tool, particularly a borescope, to be possible into the interior of the turbine blade.

11/11/2010 10:00 AM 10/002,141 033275-316

ABSTRACT

[0016] A component of a flow machine, in particular a gas turbine, includes cooling channels for a cooling medium and also at least one inspection aperture through which an inspection of the interior of the component is made possible. The component is distinguished in that the inspection aperture is arranged and dimensioned such that it simultaneously fulfills the function of a dust discharge aperture for dust or dirt particles contained in the cooling medium. The aperture which serves as both a dust discharge aperture and an inspection aperture, simplifies the inspection function, without having to provide in the component additional apertures affecting efficiency.

MARKED-UP COPY OF THE SPECIFICATION

11/11/2010 10:00 AM 10/002,141 033275-316

~~{Component of a Flow Machine, With Inspection Aperture}~~

COMPONENT OF A FLOW MACHINE, WITH INSPECTION APERTURE

Field of the Invention

[0001] The present invention relates to a component of a flow machine, particularly of a gas turbine, which has cooling channels for a cooling medium and also at least one inspection aperture through which an inspection of the interior of the component is made possible, and also a process for the inspection and/or cleaning of the interior of such a component.

Background of the Invention

[0002] For the attainment of a high efficiency factor, modern high temperature gas turbines require a carefully devised cooling system, particularly for the cooling of the highly loaded turbine blades. The turbine blades have for this purpose one or more chambers and/or channels constructed as cavities, via which a cooling medium can be supplied to the blades from the rotor side. As a rule, numerous cooling air bores are provided at the leading region of the turbine blades at their forward edge, and the cooling medium can emerge through them from the interior of the blade. A cooling air film forms on the surface in this region and protects the turbine blade from excessive heating. In the same way, corresponding cooling air bores are also present at the rear edge of the turbine blade.

[0003] A problem with such hollow components, such as turbine blades or combustion chamber elements, which are frequently cast in one piece, is represented by the poor accessibility of the interior of these components. Their inspection, for example for internal damage such as cracks, or for dirt deposits, is therefore as a rule difficult.

~~{Description of Prior Art}~~

[0004] To avoid this problem, it is known, for example from DE 198 01 804 A1, to install, in addition to the cooling air bores which are necessary in each case, one or more inspection access apertures in the outer wall of the turbine blade, through which bores the blade interior can be investigated with a corresponding inspection tool. Such an inspection aperture or inspection access aperture also makes possible the inspection of an already

built-in turbine blade, and also the cleaning from the interior of the turbine blade of dirt deposits which could lead to blockage of the very narrow cooling air bores. The ~~[said]~~ document provides for the introduction of a special cleaning tool through the inspection access aperture for this purpose.

Summary of the Invention

[0005] The present invention ~~[has as its object to develop]~~ **provides** a hollow component of a flow machine, **such as a turbine engine**, in such a manner that both the inspection and also a reduction of the danger of a blockage of the cooling air bores can be implemented in a simple manner.

~~[Summary of the Invention]~~

~~The object is attained with the component according to patent claim 1. Advantageous embodiments of the component are the subject of the dependent claims. Patent claim 6 furthermore gives a process for the inspection and/or cleaning of the interior of a component configured according to patent claim 1.]~~

[0006] The component with cooling channels for a cooling medium and also at least one inspection aperture through which inspection of the interior of the component is made possible is characterized in that the inspection aperture is arranged on the component, and is dimensioned, in such a manner that it simultaneously forms a dust discharge aperture for dust or dirt particles contained in the cooling medium.

~~[By a]~~

[0007] A "dust discharge aperture" ~~[there is]~~ **refers** to ~~[be understood here]~~ an aperture in the wall of the component by means of which particles entrained in the cooling medium emerge from the interior of the component due to their inertia. A dust discharge aperture ~~[must]~~ **should** therefore ~~[inevitably]~~ be arranged at a deflection of the channel conducting the cooling medium or at the end of a dust channel branching from this channel at a corresponding deflection. Such dust discharge apertures are already used in components of flow machines in order to prevent a blockage of the cooling channel bores. An example of an embodiment of a turbine blade with such a dust discharge aperture can be gathered from U.S.

Patent 4,820,122, for example. The interior of the turbine blade here has cooling air channels which run in a serpentine manner. The branching into the individual serpentine channels takes place ~~{already}~~ in the region of the entry of the cooling air into the turbine blade at the rotor. A straight channel extends radially as a direct extension of the inlet channel and leads directly to a dust discharge aperture at the blade tip. Particles entering with the cooling air are conveyed, due to the **force of the** cooling ~~{force {sic}}~~ **air**, directly in a straight line radially to this dust discharge aperture, while nearly dirt-free air can enter the other serpentine channels without problems. The dust particles are thus conducted out of the cooling channels into the open air ~~{sic}~~ through this dust discharge aperture or this dust hole, so that the cooling air bores ~~{proper cannot be}~~ **are not** blocked by the dust particles.

[0008] The inventor of the present invention has now discovered that inspection access apertures, by skillful arrangement, can fulfill the function of dust discharge apertures, or that dust discharge apertures, by suitable dimensioning, particularly enlargement, can serve as inspection access apertures. The dust discharge apertures **according to the invention** are ~~{here}~~ designed in size and position both so that dust is favorably discharged and also an aperture with sufficient diameter is formed in order to be able to introduce a borescope through this aperture.

[0009] The inspection aperture or inspection bore, which at the same time represents a dust discharge aperture, is preferably already considered when the component is cast and not, as is the case with the cooling air apertures, introduced by subsequent drilling. In rotating blades, this inspection and dust discharge aperture is preferably located in the neighborhood of the blade tip. In order to be able to inspect these blades even in the built-in state of the machine, these inspection and dust discharge apertures are to be arranged approximately parallel to the machine axis, if the inspection tool is to be introduced in the hot gas path of the gas turbine. If the inspection tool is to be introduced radially into the machine, a position at the blade tip is more favorable in which the inspection and dust discharge aperture runs radially of the machine axis. By the combination according to the invention of the dust discharge and the inspection function in one and the same aperture, unnecessary apertures are avoided which can lead to an undesired loss of cooling medium and thus bring about a loss of efficiency.

Brief Description of the Drawings

~~[The invention is briefly described hereinafter using embodiment examples in connection with]~~

[0010] The invention is described below with reference to the embodiments shown in the accompanying drawing, without limitation of the general concept of the invention in any way.

[0011] Fig. 1 ~~is~~ is a diagram schematically showing a section through a turbine blade ~~[which is embodied according to]~~ **in accordance with an embodiment of** the ~~[present]~~ invention~~;~~ and].

[0012] Fig. 2 is a further example, in cross section, ~~[of the embodiment]~~ of a turbine blade ~~[which is embodied]~~ according to **another embodiment of** the present invention.

Detailed Description of the Preferred Embodiments

[0013] Fig. 1 schematically shows in cross section a turbine blade with a blade foot 1, platform 2, and ~~[also]~~ blade 3. Cooling air is supplied to the turbine blade from the blade foot 1 by means of the cavity 4 visible in the cross section. A dust discharge aperture 5 is shown at the blade tip in the forward region, i.e., in the leading region of the turbine blade, and dirt particles entrained with the cooling medium are discharged, due to their inertia, from the hollow channel 4 through the said dust discharge aperture 5. Due to the high flow speed of the cooling medium at the deflection of the cooling channel 4 present at the dust discharge aperture 5, the particles, due to their large mass, take the path through the dust discharge aperture 5 and do not pass via the deflection into the further course of the cooling channel, in which relatively dust-free air thus flows. ~~[This]~~ **The** cooling air flows past the pins 6 and leaves the blade by means of apertures at the rear edge, for example, by means of a slit.

[0014] The dust discharge aperture 5 is, according to the invention, constituted with a large enough diameter for the introduction of a borescope to be possible through this aperture 5 into the interior of the turbine blade. In this manner, the interior of this component can be inspected at any time, even in the built-in state.

[0015] Finally, Fig. 2 shows a further example, in which the dust discharge aperture 5 however runs, not radially, but in the axial direction. In this example also, the blade foot 1, platform 2, and turbine blade 3 can again be seen in cross section. The cooling channel 4 runs in the same way as in Fig. 1. The dust hole 5, which in this example runs parallel to the machine axis, makes inspection possible with an inspection tool introduced in the hot gas path. The mechanism of dust extraction is the same as that in Fig. 1. In this example, the dirt particles, due to their inertia and the high flow speed of the deflected cooling medium, take the path via the channel 7 leading to the dust hole 5, while the cooling medium is deflected at the branch without problems in the direction toward the machine axis and is therefore conducted, relatively dust-free, past the pins 6 to the cooling air apertures at the rear edge of the blade. The dust hole 5 or the channel 7 leading to this are hence again constituted with a large enough diameter for the introduction of an inspection tool, particularly a borescope, to be possible into the interior of the turbine blade.

~~[List of Reference Numerals]~~

~~1-blade foot~~

~~2-platform~~

~~3-blade~~

~~4-cooling channel~~

~~5-dust discharge aperture or inspection aperture~~

~~6-pins~~

~~7-dust discharge channel]~~

~~[Abstract]~~

ABSTRACT

~~[The present invention relates to a]~~

[0016] A component of a flow machine, in particular a gas turbine, ~~[which has]~~ **includes** cooling channels ~~[(4)]~~ for a cooling medium and also at least one inspection aperture ~~[(5)]~~ through which an inspection of the interior of the component is made possible. The component is distinguished in that the inspection aperture ~~[(5)]~~ is arranged and dimensioned such that it simultaneously fulfills the function of a dust discharge aperture for dust or dirt particles contained in the cooling medium. **The aperture which serves as both** ~~[By the combination of]~~ a dust discharge aperture ~~[with]~~ **and** an inspection aperture, ~~[a simple]~~ **simplifies the** inspection function ~~[is offered]~~, without having to provide in the component additional apertures affecting efficiency.~~[(Fig. 1)]~~